COR-IP20MP 2.0 MEGAPIXEL IP CAMERA w/ VARIFOCAL LENS



General Specifications

Video Sensor: 1/3" CMOS (2 Megapixel)
Resolution: HD - 2 Megapixel - 720P - VGA Selectable
Frame Rate: 15fps @ 2 Megapixel, 30fps @ 720P
Sensitivity: 0.1 LUX, 0.0 LUX w/IR on
Lens: 3.6-16mm varifocal, Megapixel rated
DC Auto-iris Support: Yes
RAM: 256M
Flash: 16M
Video Resolution: 1600x1200, 1280x1024, 1280x960, 1280x720, 800x600, 640x480, 320x240, 176x144
Video Adjustments: Brightness, Contrast, Sharpness, Backlight Compensation, Night Mode
Triple Streaming: Yes
Image Snapshot: Yes
Full Screen Monitoring: Yes
Privacy Mask: Yes, 3 zones
Video Compression: H264/JPEG/MPEG4 (3GPP only)
Video Bitrate Adjustment: CBR, VBR
Motion Detection: Yes, 3 zones
Triggered Event: eMail, FTP, Save image to SD card, Relay
Pre/Post Alarm: Yes, configurable
CPU: ARM 9, 32-bit RISC
ICR: Mechanical IR cut filter
Infrared System: 35 IR LEDs
Infrared Range: 65' (20m)
I/O: 1 in, 1 relay out
Power Over Ethernet: Yes (POE)
Firmware Upgrade: HTTP mode, remotely
Power: 12VDC @ 500mA (nominal)
Dimensions w/Light Shield: 3" x 3" x 6.75" (76mm x 76mm x 171mm)
Network Specifications
Ethernet: 10/100 Base T
Protocols: HTTP, TCP/IP, UDP, SMTP, FTP, PPoE, DHCP, DDNS, NTP, UPnP, 3GPP
Security: Password based
Browser OS: Windows 2000/XP with MS IE 6.0 or greater

Users: Up to 10 simultaneous connections

- 2 MEGAPIXEL SENSOR
- 3.6-16mm VARIFOCAL LENS
- TRIPLE STREAMING
- POE Power

2 Megapixel Network IP Security Camera

The COR-IP22MP uses a 2-Megapixel video sensor and an auto-iris equipped, Megapixel rated varifocal lens to provide images in HD and VGA resolutions. Features like POE, triple streaming, and easy connection to cell phones and portable devices (no app or additional software required) makes this camera an easy-to-use, easy-to-install addition to your surveillance network.



Video picture output, generated by a 1/3" CMOS 2M video sensor, can be adjusted in a variety of ways including resolution, brightness, contrast and more.



Environmental Specifications

Operating Temperature: -10° C to 50° C (10% to 90% humidity, NC)

Weatherproof Rating: IP66 (outdoor or indoor placement)

