960H OUTDOOR IP BULLET w/ IR & VARIFOCAL



FEATURES

- DAY / NIGHT MODE, BUILT-IN ICR
- POWER OVER ETHERNET
- VANDAL-PROOF, IP67
- 35 PCS IR LED 25 METERS
- 3D+2D DNR
 - FREE 36 CH RECORDING SOFTWARE

SPECIFICATIONS		NETWORK	
VIDEO SENSOR	1/2.7" 2 MP CMOS	SECURITY	Password Protection, IP Address Filtering, User HTTPS encrypted data transmission,802.1x portbased authen-
RESOLUTION	720p, 1080p, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1280x720, 800x600, 640x480, 320x240, 176x144		tication for network protection,QoS/ DSCP
LENS	3.3~16mm Varifocal	PROTOCOLS	TCP/IP, UDP, DHCP, PPPoE,
EFFECTIVE PIXELS (HXV)	1920 x1080		HTTP, DDNS, DynDNS, NTP, FTP, SMTP,HTTPS,SNMP,UDP, RTSP, IEEE802.1X,3GPP, UPnP, IPv4/
ANGLE OF VIEW	23.6° ~ 97.9°		v6,SAMBA, Bonjour
ILLUMINATION	0.1 lux @ F1.2, 0 Lux (IR on,0.0 LUX)	APPLICATION INTERFACE	CGL/ ONIVIE Support
INFRARED SYSTEM	Automatic, 35 IR LEDs (850nm), up to 25 meters range	VIEWING REQUIREMENTS	WIN XP, VISTA, or 7, MS Internet Explorer 6+
COMPRESSION	H.264 / M-JPEG / MPEG4	ETHERNET	10/100 Base-T
SHUTTER SPEED	1/5 s to 1/10000 Selectable	HARDWARE	
STREAMING	Dual streaming supported	CPU	ARM 9, 32-Bit RISC
VIDEO OUT	Yes	RAM	256m
USER ADJUSTMENTS	Brightness, Contrast, Sharpness, BLC, Night Mode	FLASH RELAY OUTPUTS	16m N.O. & N.C
SNAPSHOT & ZOOM	Yes	AUDIO FORMAT MICROPHONE INPUT	G.711 audio
FULL SCREEN MONITORING	Yes	2-WAY COMMUNICATION	Supported (requires speaker, & mic. not included)
PRIVACY MASK	Yes, 3 zones	POWER OVER ETHERNET	Yes (POE)
BITRATE ADJUST	CBR, VBR	PHYSICAL	
DNR	On/Off	OPERATING TEMP	-10 °C ~ 50 °C (14 °F ~ 122 °F)
CERTIFICATIONS	1	CASE	Hardened aluminum alloy
CE	Yes	ANTI-VANDAL	IP67 rated tough metal construction, dome built to withstand heavy blows,
FCC	Yes		protected cable routing.
RoHS	Yes	BRACKET	Cable feed through
		DIMENSIONS	5.7" long, 3.75" wide
INCLUDED ACCESSORIES		WEIGHT	2.4 lbs
Power Adapter, Power Cable, CD-ROM (User Manual,Includes Bundled Viewing Software)		POWER	12 VDC:5.8w (IR on), 3.8w (IR off) PoE:7.7w(IR on)4,8w. (IR off)

