

1080p (1929 x 1080) SDI OUTDOOR IR TURRET CAMERA

1080P
HD CCTV



KEY BENEFITS

- HIGH DEFINITION 1080P OVER COAX
- HIGH POWER INFRARED
- SMART NOISE REDUCTION
- 2.8-12MM MEGAPIXEL LENS
- INTEGRATED LENS SEPARATOR
- DIGITAL DEFOG

MODEL : EX-HD88V

Designed with aesthetics in mind, the HD88V is produced for industrial applications where image adjusting is vital. The high power infrared system is crucial for capturing images on a pitch black night.

- Vandal resistant all metal housing
- Ball-in-Socket design
- Highlight- Backlight compensation
- Advanced OSD menu
- Automatic gain control



SPECIFICATIONS

Video Sensor	1/3" Panasonic CMOS 16:9 Full HD sensor
Resolution	1920x1080P 2.1 Megapixel
Lens	Varifocal Auto-Iris 2.8-12mm Megapixel rated IR cut filter lens F1.2
Illumination Range	0.5 LUX (0.0 LUX with IR on)
Video Output	SDI High Definition Output
White Balance	ATW (w/SET option), (OSD Control)
IR Range	100ft visual distance
IR LED Array	48 IR LEDs
Shutter	AES (OSD Control)
Gain Control	AGC (OSD Control)
Scanning System	Progressive Scan
Wide Dynamic Range	Yes, with Low/Middle/High & Off (OSD Control)
Dynamic Noise Reduction	2DNR, 3DNR, SMART DNR
Mechanical IR Filter	Mechanical Day/Night ICR-IR Cut Filter
BLC & HLC	Yes (OSD Control)
Image Control	Sharpness, brightness, color control (OSD Control)
Privacy	8 zone (OSD Control)
Day / Night	Adjustable (OSD Control)
Weatherproof Rating	IP65 (indoor/outdoor)
Vandal Resistance	Hardened case, cable feed-through
Power	12VDC 500mA (sold separately)
Housing	All metal (Ball-in-Socket Design)
Dimension (inches)	4.2"(H) x 4.7"(W) (107mm x 120mm)
Weight	1.1 (lbs) 500(g)

Additional OSD Options:
Exposure-wb-manual-special-cam-title-motion-privacy-park-line-image-adj-comm-adj-language-area-state-height-width-mirror-font-contrast-sharpness



LEADERS IN TECHNOLOGY CHARGING AHEAD

WWW.ECLIPSECCTV.COM