



SPECIFICATIONS	
Video Sensor	1/3" Panasonic CMOS
Resolution	1920 x 1080 (1080p/30fps)
	1280 x 720 (720p/60fps)
Asking Divole	(Analog : 700TVL)
Active Pixels Total Pixels	1944(H) x 1092(V) = 2,122,648
	2010(H) x 1108(V) = 2,227,080
Lens type Zoom Ratio	x20, Day & Night Zoom Lens
	Optical x20 , Digital x32 f = 4.7 mm ~ 94 mm
Focal length	
Aperture Ratio Focus distance	F1.6 (wide) ~ F3.5 (tele)
Minimum Illumination	
Minimum illumination	Color: 0.5Lux, BW: 0.1Lux Color DSS: 0.002 lux, BW DSS: 0.001 lux
Output format	1080p / 720p
S/N Ratio	More than 50dB(AGC off)
Video Output	HD Video Out, HD-SDI, CVBS
WDR/ BLC/ HLC	Off / On
Brightness	1 ~ 15 steps
Motion Detection	Off / 4 positions
Sharpness	Off / On
Smart IR /Defect compensation	Off / On
Pattern Generation/ CVBS output/	Off / On
Shading / Defog	Off / On
Day & Night	ATW / Preset / Indoor / Outdoor / Man-
White Balance	O (Position, Area Ajustable)
Privacy Mask	Off / 32 positions
DNR	Off / Auto / Low / Middle / High
Mirror	Off / H / V / H+V
E zoom	Off / x2 ~ x32
Exposure	Auto / Manual
Gain control	Off / On (Auto max.30dB)
Shutter speed	1/30(1/25) ~ 1/30,000
Digital Shutter Speed	Off / x2 ~ x4

KEY BENEFITS

- DIGITAL 1080P HIGH DEFINITION OVER COAX
- 20X OPTICAL ZOOM
- DIGITAL NOISE REDUCTION
- DAY & NIGHT (ICR)
- 4.7mm ~ 94mm FOCAL LENGTH
- INTELLIGENT MOTION DETECTION

Designed with high quality in mind, the HDZ20 is perfect for industrial applications where image adjusting is vital. Dual scan true wide dynamic range allows for the best picture in a number of bright lighting condition. The high power infrared system is crucial for capturing images on a pitch black night. A high-end chipset makes all the difference, don't be fooled by cheap look-alikes.

- High light compensation function
- Privacy mask function
- Full OSD Menu

* COMMUNICATION	
Protocol	Pelco -D / Pelco-P / VISCA
Baud Rate	2400 / 4800 / 9600 / 19200 / 38400 / 57600
Frequency	60Hz / 50Hz
Scanning System	Progressive
* POWER	
Operating Temperature	-10°C ~ 50°C
Operating Temperature	-20° C~ 60°C
Power Consumption	Max 500mA
Power	DC 12V ± 10%
* PHYSICAL	
Dimensions (W x H x D)	128(L) x70(W) x 67(H) (mm) 5.0(L) x 2.75(W) x 2.63(H) (inches)
Weight	.56(kg) 1.23 (lbs)

SPECIFICATIONS

Additional OSD Options: Exposure-wb-manual-special-cam-title-motion-privacypark-line-image-adj-comm-adj-language-area-stateheight-width-mirror-font-contrast-sharpness

