

ECL-IP22MP

2 Megapixel Network IP Camera with POE

The ECL-IP22MP uses a 2-Megapixel video sensor and an auto-iris equipped, Megapixel rated varifocal lens to provide images in HD and VGA resolutions. Features like POE, triple streaming, and easy connection to cell phones and portable devices (no app or additional software required) makes this camera an easy-to-use, easy-to-install addition to your surveillance network.

- ✓ 2 MEGAPIXEL SENSOR
- ✓ POE Power
- ✓ 3.6-16mm VARIFOCA LENS
- ✓ TRIPLE STREAMING

General Specifications

Video Sensor: 1/3" CMOS (2 Megapixel)
Resolution: HD – 2 Megapixel – 720P – VGA Selectable
Frame Rate: 15fps @ 2 Megapixel, 30fps @ 720P
Lens: 3.6-16mm varifocal, Megapixel rated with Auto-Iris
Triple Streaming: Yes
Sensitivity: 0.1 LUX, 0.0 LUX w/IR on
Video Resolution: 1600x1200, 1280x1024, 1280x960, 1280x720, 800x600, 640x480, 320x240, 176x144
Video Adjustments: Brightness, Contrast, Sharpness, Backlight Compensation, Night Mode
Memory: 16G Internal SD CARD
2-Way Communication support: Connectors for microphone & speaker provided (mic. & speaker sold separately)
Attached Video Cable: Composite Video Output (BNC)
Full Screen Monitoring: Yes
Privacy Mask: Yes, 3 zones
Video Compression: H264/JPEG/MPEG4
Motion Detection: Yes, 3 zones
Triggered Event: eMail, FTP, Save image to SD card, Relay
Image Snapshot: Yes
Sensor/Alarm: Connector block with NC/NO sensor inputs, GND, and ALARM Output
Pre/Post Alarm: Yes, configurable
ICR: Mechanical IR cut filter
Infrared System: 35 IR LEDs
Infrared Range: 65' (20m)
I/O: 1 in, 1 relay out
Power Over Ethernet: Yes (POE)
Firmware Upgrade: HTTP mode, remotely
Power: 12VDC @ 500mA (nominal)
Dimensions: 3" x 3" x 6.75" (76mm x 76mm x 171mm)

Network Specifications

Ethernet: 10/100 Base T
Protocols: HTTP, TCP/IP, UDP, SMTP, FTP, PPOE, DHCP, DDNS, NTP, UPnP, 3GPP
Security: Password based
Browser OS: Windows 2000/XP with MS IE 6.0 or greater
Users: Up to 10 simultaneous connections

Environmental Specifications

Operating Temperature: 0° C to 50° C (10% to 90% humidity, NC)
Weatherproof Rating: IP66 (outdoor or indoor placement)



Video picture output, generated by a 1/3" CMOS 2M video sensor, can be adjusted in a variety of ways including resolution, brightness, contrast and more.

